

FLASH CURE UNITS



F-Flash

On/off breaker switch (optional locking casters)
Flashes in 7 to 10 seconds
3 year heater warranty

F1-18

240V, 1750 Watt High Density Infrared Heater, 18" (46 cm) sq.



REDFlash

Locking casters & adjustable heat control (optional super heavy duty stand)
Standard output heater flashes in 7 seconds, high output heater flashes in 4 seconds
10 year heater warranty

SHHD-STAND Super Heavy Duty Stand Upgrade

R-18-240

240V, 2000 Watt High Density Infrared Heater, 18" (46 cm) sq.

R-18-240-HO

240V, High Output 3500 Watt High Density Infrared Heater, 18" (46 cm) sq.

R-1824-240

240V, 3500 Watt High Density Infrared Heater, 18" x 24"(46 x 61 cm) sq.



AUTOFlash

Adds motor for **automatic head swing** with foot pedal & timer
Standard output heater flashes in 7 seconds, high output heater flashes in 4 seconds
10 year heater warranty

0 - 30 second timer provides

consistent curing every time!

RedFlash 18" (46 cm) sq. &
AutoFlash with optional
Super Heavy Duty Stand shown

Buy as a complete unit or upgrade
to automate your existing system
(can fit other brand flashes/spot heaters).

SHHD-STAND Super Heavy Duty Stand Upgrade

R-18-240-AF

240V, 2000 Watt High Density Infrared Heater, 18" (46 cm) sq., standard stand w/ 240V AutoFlash

R-18-240-HO-AF

240V, High Output 3500 Watt High Density IR Heater, 18" (46 cm) sq., std. stand w/ 240V AutoFlash

R-1824-240-AF

240V, 3500 Watt High Density IR Heater, 18" x 24"(46 x 61 cm) sq., std. stand w/ 120V AutoFlash

	REDFLASH		F-FLASH
	R-18-240	R-1824-240	F1-18
Locking Casters	Std	Std	Opt
Temperature Control	Std	Std	N/A
AutoFlash Upgrade	Opt	Opt	N/A
High Output Heater	Opt	N/A	N/A
Super Heavy Duty Stand	Opt	Opt	N/A
Head Leveler	Std	Std	N/A

Specifications Comparison



	REDFLASH		F-FLASH
Models	R-18-240	R-1824-240	F1-18
Heater Warranty	10 Year	10 Year	3 year
Bumper to Bumper Warranty	3 Year	3 Year	3 year
Overall Width	45" (115 cm)	51" (130 cm)	45" (115 cm)
Overall Height [Std. Stand casters + 2" (5 cm)]	31"- 47" (79 - 119 cm)	31"- 47" (79 - 119 cm)	31"- 47" (79 - 119 cm)
Overall Height (Super Heavy Duty Stand)	35"- 43" (89 - 109 cm)	35"- 43" (89 - 109 cm)	N/A
Heater Size	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)	18" x 18" (46 x 46 cm)
Unit Warm Up Time	6 min. (240V)	12 min.	15 min.
Heater Wattage	2,000 or 3,500 Watt Heater	3,500 Watt Heater	1,750 Watt Heater
Electrical Specs*	240V/9A/2,000W/NEMA 6-15P Plug	240V/16A/3,500W/NEMA 6-20P Plug	240V/8A/1,750W/NEMA 6-15P Plug
(Requires dedicated line. 50/60 HZ for all units.)	240V/16A/3,500W/NEMA 6-20P Plug		
Electrical Specs - AutoFlash (Requires dedicated line. 50/60 HZ for all units.)	220-240V/1A/NEMA 6-15P Plug	220-240V/1A/NEMA 6-15P Plug	
Shipping Weight-Head**	35 lbs (16 kg)	43 lbs (19.5 kg)	(Head + Legs) 44 lbs (20 kg)
Shipping Weight - Legs** (std. stand)	22 lbs (10 kg)	22 lbs (10 kg)	(Post Tube) 4 lbs (1.8 kg)
Shipping Weight - Legs** (SHHD stand for manual flash) ships in 2 packages	38 lbs (17 kg) 10 lbs (4.5 kg)	38 lbs (17 kg) 10 lbs (4.5 kg)	N/A
Shipping Weight - AutoFlash kit**	51 lbs (25 kg)	51 lbs (25 kg)	N/A
Shipping Weight - AutoFlash** (SH-LEGS-AF stand)	15 lbs (7 kg)	15 lbs (7 kg)	N/A
Shipping Weight - AutoFlash** (SHHD stand)	38 lbs (17 kg)	38 lbs (17 kg)	N/A
Shipping Dimensions - Head**	26" x 29" x 5" (66 x 74 x 13 cm)	26" x 35" x 6" (66 x 90 x 15 cm)	(Head + Legs) 28" x 24" x 7" (71 x 61 x 18 cm)
Shipping Dimensions - Legs** (Standard Stand)	36.5" x 6.5" x 2.5" (92.7 x 17 x 7 cm)	36.5" x 6.5" x 2.5" (92.7 x 17 x 7 cm)	(Post Tube) 41" x 3 x 3" (104 x 8 x 8 cm)
Shipping Dimensions - Legs** (SHHD - Super Heavy Duty Stand for manual flash) ships in 2 pkgs.	29" x 32" x 4" (74 x 81 x 10 cm) 32" x 9" x 4" (81 x 23 x 10 cm)	29" x 32" x 4" (74 x 81 x 10 cm) 32" x 9" x 4" (81 x 23 x 10 cm)	N/A
Shipping Dimensions - Auto Flash kit**	31" x 22" x 14" (79 x 56 x 36 cm)	31" x 22" x 14" (79 x 56 x 36 cm)	N/A
Shipping Dimension - AutoFlash** (SH-LEGS-AF stand)	29" x 32" x 4" (74 x 81 x 10 cm)	29" x 32" x 4" (74 x 81 x 10 cm)	N/A
Shipping Dimension - AutoFlash** (SHHD stand)	39" x 32" x 4" (99 x 81 x 10 cm)	39" x 32" x 4" (99 x 81 x 10 cm)	N/A

*If extension cord is required, recommend using minimum 10 gauge wire with maximum 12' (3.6 m) length. For longer lengths, consult electrician.



International tel: +44 1282 841777

Tel: 0845 224 1204 Fax: 0845 224 1205

Email: info@dalesway.co.uk Web: www.dalesway.co.uk